

Hose clamps and other connection and installation elements



Master-Grip quick action clamp

Special hose clamp for spiral hoses with a right turning

Applications

Special hose clamp for securing spiral hoses with a right turning: Flamex, Master-PUR, Master-PVC and Master-SANTO.

Standard production:

- Clamping ranges from 75/82 mm up to 500/507 mm
- Clamp band, bridge and lock: stainless steel 1.4301



Hose clamp, bolt clamp

Large strip hose clamp of galvanised steel

Applications

For attaching medium weight and heavy spiral hoses onto connecting branches on mobile and stationary units.

Standard production:

- Clamping ranges from 32/35 mm up to 500/518 mm
- Clamp band and screw: galvanised steel

Available on request:

- in stainless steel



Hose clamp, with worm gear drive

Hose clamp

Applications

For attaching lightweight spiral hoses onto connecting branches on mobile and stationary units.

Standard production:

- Clamping ranges from 25/42 mm up to 500/520 mm
- Clamp band and screw casing: steel

Available on request:

- in stainless steel



Hose reducer

symmetrical reducer of rolled sheet steel

Applications


Extending, connecting and attaching lightweight or medium weight hoses.

Standard production:

- reducers: DN 80/50 mm up to DN 300/250 mm

Available on request:

- in stainless steel



Hose connector

Applications

Extending, connecting and attaching lightweight or medium weight hoses.

Standard production:

- DN 50 - DN 900

Available on request:

- in stainless steel



Heat shrink cuff

Applications

Leak proof method of connecting or attaching spiral hoses and fittings.

Standard production:

- skinking range: 54/18 mm up to 375/265 mm
- Colour: black

Temperature resistant:

- -55°C up to +110°C